


- 1.Design conforms to AS2638.2 .
- 2.Face to Face according to AS2638.2.
- 3.Flanges standard AS2129 Table D.
- 4.Pressure test according to AS2638.2.
- 5.Coating to AS4158

DN	L	ΦD	ΦD1	ΦD2	f	n-Φd	b	H	W
80	203	185	146	122	3	4-Φ18	18	265	180
100	229	215	178	154	3	4-Φ18	20	307	200
150	267	280	235	211	3	8-Φ18	23	395	280
200	292	335	292	268	3	8-Φ18	23	500	320
225	305	370	324	300	3	8-Φ18	24	540	320
250	330	405	356	328	3	8-Φ22	24	585	320
300	356	455	406	378	4	12-Φ22	30	680	360

No.	Part	Material	Q'ty	Remarks
13	Dust Guard	NBR/EPDM		
12	Bolt	Galvanized steel		
11	Handwheel	Ductile iron		
10	Bonnet Gland	Ductile iron		
9	Bolt	Galvanized steel		
8	O-Ring	NBR/EPDM		
7	Washer	Al bronze		
6	Stem	SS420		
5	Bonnet	Ductile iron		
4	Stem Nut	Brass		
3	Wedge	Ductile iron+EPDM		
2	Bonnet Gasket	EPDM		
1	Body	Ductile iron		

DRN	Wang	WEIGHT		MATERIAL
CHK		SCALE		Gate Valve
APP		DATE	07/19/2024	
				CZ0015
				REV