


- 1.Design conforms to AS2638.2 .
- 2.Face to Face according to AS2638.2.
- 3.Flanges drilling according to AS2129 Table E.
- 4.Pressure test according to AS2638.2.

21	Disc	Ductile iron+EPDM		
20	Stem nut	Brass		
19	Split pin	SS		
18	Pin	Carbon steel		
17	Nut	Galvanized steel		
16	Packing	EPDM		
15	Stem	SS420		
14	Washer	Brass		
13	Nut	Galvanized steel		
12	Handwheel	Ductile iron		
11	Nut	Galvanized steel		
10	Gland	Ductile iron		
9	Bolt	Galvanized steel		
8	Nut	Galvanized steel		
7	Washer	Galvanized steel		
6	Yoke	Ductile iron		
5	O-ring	EPDM		
4	V-ring	EPDM		
3	Bonnet	Ductile iron		
2	Gasket	EPDM		
1	Body	Ductile iron		
No	Name	Material	Q'ty	Remark

SIZE	L	D	D1	D2	b	n-d	H
50	178	150	114	90	18	4-18	423
65	190	165	127	103	18	4-18	450
80	203	185	146	122	18	4-18	535
100	229	215	178	154	20	8-18	590
150	267	280	235	211	23	8-22	790
200	292	335	292	268	23	8-22	974
250	330	405	356	328	24	12-22	1185
300	356	455	406	378	30	12-26	1375

DRN	Wang	WEIGHT		MATERIAL
CHK		SCALE		Gate Valve
APP		DATE	07/19/2024	
				CZ0020
				REV