


1. Flange drilling according to EN1092-2 PN10/16.
2. Pressure test according to API598.

DN	L	D	EN1092-2 PN10			EN1092-2 PN16			b	H
			D1	n-d	D2	D1	n-d	D2		
50	203	165	125	4-19	99	125	4-19	99	19	70
65	216	185	145	4-19	118	145	4-19	118	19	74
80	241	200	160	8-19	132	160	8-19	132	19	81
100	292	220	180	8-19	156	180	8-19	156	19	93
125	330	250	210	8-19	184	210	8-19	184	19	112
150	356	285	240	8-23	211	240	8-23	211	19	126
200	495	340	295	8-23	266	295	12-23	266	20	164
250	622	400	350	12-23	319	355	12-28	319	22	195
300	698	455	400	12-23	370	410	12-28	370	24.5	229

7	Cover Bolt	Stainless Steel		
6	Hinge Pin	SS420		
5	Cover	GGG50		
4	Plug	Stainless Steel		
3	Gasket	EPDM		
2	Disc	DI + EPDM		
1	Body	Ductile Iron		
No	Name	Material	Q'ty	Remarks
DRN	Wang	WEIGHT	MATERIAL	
CHK		SCALE	Check Valve	
APP		DATE		
			CC0005	
			REV	20240720a