



Design standard: EN1349/EN1074-5
 Face to Face: EN1349:2000/1074-2000
 Flange Drilling: EN1092-2-PN10/PN16
 Pressure Test: EN12266, API598, ISO5208
 This valve is a pressure reducing valve used to maintain
 line pressure.

DN	L	D	D1	EN1092-2-PN10		EN1092-2-PN16		b
				D0	n x φd	D0	n x φd	
50	230	165	99	125	4x19	125	4x19	19
65	290	185	118	145	4x19	145	4x19	18
80	310	200	132	160	8x19	160	8x19	18
100	350	220	156	180	8x19	180	8x19	18
150	480	285	211	240	8x23	240	8x23	18
200	600	340	266	295	8x23	295	12x23	20
250	730	400	319	350	12x23	355	12x28	22
300	850	460	370	400	12x23	410	12x28	24.5

IBN		WEIGHT		MATERIAL	
CRK		SCALE			
APP		DATE	07/02/2000	Pilot solenoid Control valve	

Hiwa

CM0006

REV 200002A

This document is the property of Hiwa Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden.
 Failure to comply will incur a liability for damages.

<http://www.hiwa.cn> Website
 sales@hiwa.cn Email

98-593-8077200 Phone
 98-593-8077233 FAX

Hiwa Valve Industry Co.
 No.36 Minlin Road New Hi-Tech Industry
 Zone Zibo Shandong China 255008 p.c.