



- 1.Flange drilling according to AS2129-TableD/E
- 2.Pressure test according to ISO5208
- 3.Coating is to AS/NZS 4158

Size	DN	L	AS2129-Table D			AS2129-Table E			b	H	H1
			D	D1	nxd	D	D1	nxd			
4"	100	352.4	215	178	4x18	215	178	8x18	19	222.9	294.9
5"	125	416	255	210	8x18	255	210	8x18	21	261.3	357.6
6"	150	470	280	235	8x18	280	235	8x22	21	306.9	429.2
8"	200	543	335	292	8x18	335	292	8x22	22	377.9	558.3
10"	250	660.4	405	356	8x22	405	356	12x22	30.2	438.2	657
12"	300	762	455	406	12x22	455	406	12x26	31.8	510.9	768.6
14"	350	946.3	525	470	12x26	525	470	12x26	35	606	890.2
16"	400	1079	580	521	12x26	580	521	12x26	36.6	692.3	1009.4
18"	450	1168	640	584	12x26	640	584	16x26	39.7	756.6	1114
20"	500	1275	705	641	16x26	705	641	16x26	42.9	873.3	1295.4
24"	600	1418	825	756	16x30	825	756	16x33	47.7	1027.1	1530.2

No.	Part Name	Material
1	Body	Cast iron
2	Bonnet	Cast iron
3	Screen	SS304
4	Bonnet Gasket	Graphite
5	Plug	Galvanized steel
6	Bolt	Galvanized steel
7	Washer	Galvanized steel

DRN	wang	WEIGHT		MATERIAL	
CHK		SCALE		Y-Strainer	
APP		DATE	07/19/2024	CS0010	
				REV	20240719a