



Item	Part Name	Material	Item	Part Name	Material
1	Body	A536	7	Seat	PTFE
2	Bushing nut	Stainless Steel	8	Elastic body	Silica gel
3	Bushing	Stainless Steel	9	Spacer	Stainless Steel
4	Spring	65Mn	10	Oring	Silica gel
5	Bushing	Stainless Steel	11	Bushing	Stainless Steel
6	Disc	CF8M+PTFE	12	Plug	Stainless Steel

Product standad: API609
 Face to face: EN558-20
 Flange drilling: ASME B16.5
 Test standard: API598
 Pressure : CLASS 150

DN	L	ASME B16.5		ISO5211			□a	H0
		ΦD1	n-Φd	Top Flange	ΦD0	n1xΦd1		
50	43	120.7	4-19	F05	50	4X8	11	21
65	46	139.7	4-19	F05	50	4X8	11	17
80	46	152.4	4-19	F05	50	4X8	11	20
100	52	190.5	8-19	F05	50	4X8	14	19
125	56	215.9	8-22	F07	70	4X10	17	19
150	56	241.3	8-22	F07	70	4X10	17	24
200	60	298.5	8-22	F07	70	4X10	22	27
250	68	362	12-25	F10	102	4x12	22	29
300	78	431.8	12-25	F10	102	4x12	27	30

DRN	wang	WEIGHT		MATERIAL	
CHK		SCALE		Butterfly Valve	
APP		DATE	07/20/2024	CB0009	
				REV	20240720a

This document is the property of Huihua Valve Industry Co.
 Distribution of this document without the written consent of the owner is strictly forbidden
 Failure to comply will incur a liability for damages
 http://www.hiwa.cn Website
 sales@hiwa.cn Email
 86 - 533 - 6077200 Phone
 86 - 533 - 6077233 FAX
 Huihua Valve Industry co.
 No.36 MinAn Road New Hi-Tech Industry
 Zone Zibo Shandong China 255088 p.c