



**Specification:**

- 1.Design standard: MSS SP-67
- 2.Face to face: ASME B16.10
- 3.End Connection:AWWA C606
- 4.Top Flange:ISO5211
- 5.Working Pressure: PN16

Size	Name	Material	Q'ty	Remark
1	Body	Ductile Iron GGG40		
2	Disc	DI GGG40 with EPDM		
3	Stem	SS420		
4	Bushing	PTFE		
5	O ring	EPDM		

Size		L	H1	H2	H3	ISO 5211	φN	ΦC1	n1-Φd1	□A
mm	inch									
DN50	2"	86	70	101.6	29	F05	65	50	4-8	9
DN65	2 1/2"	97	75	106.2	29	F05	65	50	4-8	9
DN80	3"	97	82	112.5	29	F05	65	50	4-8	9
DN100	4"	116	100	135.4	29	F07	90	70	4-10	11
DN125	5"	133	100	138	29	F07	90	70	4-10	14
DN150	6"	134	115	163	29	F07	90	70	4-10	14
DN200	8"	148	150	204	35	F10	125	102	4-12	17
DN250	10"	159	200	250	35	F10	125	102	4-12	22
DN300	12"	163	230	275	35	F10	125	102	4-12	22

DRN	wang	WEIGHT		MATERIAL
CHK		SCALE		Butterfly Valve
APP		DATE	07/22/2024	
				B90G
				REV

Huihua Valve Industry Co. No.36 MinAn Road New Hi-Tech Industry Zone Zibo Shandong China 255088 p.c  
 Phone 86 - 533 - 6077200 FAX 86 - 533 - 6077233  
 Website http://www.hiwa.cn Email sales@hiwa.cn  
 This document is the property of Huihua Valve Industry Co. Distribution of this document without the written consent of the owner is strictly forbidden. Failure to comply will incur a liability for damages.