



- Specification :**
- 1.General: API609
  - 2.Face to face: DIN3202-K1
  - 3.Inspection and test: API 598
  - 4.Mounting pad: ISO 5211
  - 5.Flange drill: EN1092-2 PN10/16

DN	L	H1±5 (Max)	H2±5 (Max)	H3	EN1092-2 PN10		EN1092-2 PN16		Flange No	φN	φC1	n1-φx0	hXh
					φC	n-φd	φC	n-φd					
50	43	161	82.5	29	125	4-19	125	4-19	F05	65	50	4-φ8	9X9
65	46	175	92.5	29	145	4-19	145	4-19	F05	65	50	4-φ8	9X9
80	46	181	100	29	160	8-19	160	8-19	F05	65	50	4-φ8	9X9
100	52	200	110	29	180	8-19	180	8-19	F07	90	70	4-φ10	11X11
125	56	213	125	29	210	8-19	210	8-19	F07	90	70	4-φ10	14X14
150	56	226	142.5	29	240	8-23	240	8-23	F07	90	70	4-φ10	14X14
200	60	260	170	35	295	8-23	295	12-23	F10	125	102	4-φ12	17X17
250	68	292	202.5	35	350	12-23	355	12-28	F10	125	102	4-φ12	22X22
300	78	337	242	35	400	12-23	410	12-28	F10	125	102	4-φ12	22X22

Item	Part name	Material	Qty	Remark
6	Seal Ring	EPDM		
5	Bushing	PTFE		
4	Seat	NBR/EPDM		
3	Stem	SS416		
2	Disc	SS304		
1	Body	Ductile Iron		

DRN	Wang	WEIGHT	
CHK		SCALE	
APP		DATE	07/20/2024

**Hiwa**

REV	20240720a	MATERIAL	Butterfly Valve
			B10U-HJ