



- Specification:
- 1.General: API609
 - 2.Face to face: DIN3202-K1
 - 3.Inspection and test: API 598
 - 4.Mounting pad: ISO 5211
 - 5.Flange drill: EN1092-2 PN16

DN	L	EN1092-2-PN16		H1±5 (Max)	H2±5 (Max)	H3	ISO5211				H
		ØC	n-M				ØN	ØC1	TOP	ØN	
50	43	125	4-M16	57	143	29	F05	65	50	4-Ø8	9
65	46	145	4-M16	68	155	29	F05	65	50	4-Ø8	9
80	46	160	8-M16	82	160	29	F05	65	50	4-Ø8	9
100	52	180	8-M16	100	181	29	F07	90	70	4-Ø10	11
125	56	210	8-M16	112	194	29	F07	90	70	4-Ø10	11
150	56	240	8-M20	126	202	29	F07	90	70	4-Ø10	14
200	60	295	12-M20	162	240	35	F10	125	102	4-Ø12	17
250	68	350	12-M24	193	272	35	F10	125	102	4-Ø12	22
300	78	400	12-M24	236.5	318	35	F10	125	102	4-Ø12	22

7	Pin	SS		
6	Seal Ring	EPDM		
5	Bushing	PTFE		
4	Seat	EPDM		
3	Stem	SS420		
2	Disc	DI		
1	Body	CI/DI		
Item	Part name	Material	Q'ty	Remark
Wang		MATERIAL		
DIN		WEIGHT		
CHK		SCALE		
APP		DATE		
		07/20/2024		
		Butterfly Valve		
		B15L-YX		

Hiwa

REV

20240720a