



Specification:

- 1.General: API609
- 2.Face to face: DIN3202-K1
- 3.Inspection and test: API 598
- 4.Mounting pad: ISO 5211
- 5.Flange dri: EN1092-2 PN10/16

DN	L	EN1092-2		H1	H2	H3	ISO5211				H
		PN10	PN16				TOP	ΦN	ΦC1	n1-Ød1	
50	43	125	125	57	143	29	F05	65	50	4-Ø8	9
65	46	145	145	68	155	29	F05	65	50	4-Ø8	9
80	46	160	160	82	160	29	F05	65	50	4-Ø8	9
100	52	180	180	100	160	29	F07	90	70	4-Ø10	11
125	56	210	210	112	181	29	F07	90	70	4-Ø10	14
150	56	240	240	126	194	29	F07	90	70	4-Ø10	14
200	60	295	295	162	240	35	F10	125	102	4-Ø12	17
250	68	350	355	193	272	35	F10	125	102	4-Ø12	22
300	78	400	410	236.5	318	35	F10	125	102	4-Ø12	22

Size	Name	Material	Qty	Remark
1	Body	Cast iron		
2	Disc	Ductile iron		
3	Stem	SS420		
4	Seat	EPDM		

DN	Wang	WEIGHT	MATERIAL
CHK		SCALE	Butterfly Valve
APP		DATE	B15W-YX

Hiwua

REV 20240720a