


Technical standard
 1. Normal pressure: 2.5Mpa
 2. Working medium: Water, Non-corrosive liquids
 3. Working temperature: 0°C < T ≤ 120°C
 4. Pipe thread conform to ISO 228(GB/T7307)

DN	SIZE	L	H
15	G 1/2	80	115
20	G 3/4	85	115
25	G1	100	120
32	G1 1/4	110	140
40	G1 1/2	120	140
50	G2	150	150

No	Name	Material	Q'ty	Remark
1	Body	H59	1	
2	Disc	PTFE	1	
3	Seat	H59	1	
4	O-ring	EPDM	1	
5	Bonnet	H59	1	
6	Connect shaft	H59	1	
7	Stem	H59	1	
8	O-ring	EPDM	1	
9	Adjust Shaft	H59	1	
10	O-ring	EPDM	2	
11	O-ring	EPDM	2	
12	Circlip	Stainless steel	1	
13	Screw	H59	1	
14	Cap	H59	1	
15	Hand wheel	PA66	1	

DRN	Wang	WEIGHT		MATERIAL
CHK		SCALE		Brass on-off control balancing valve
APP		DATE	07/19/2024	
				CM0025
				REV

Hiuhua Valve Industry Co. No.36 MinAn Road New Hi-Tech Industry Zone Zibo Shandong China 255088 p.c
 86 - 533 - 6077200 Phone 86 - 533 - 6077233 FAX
 http://www.hiwa.cn Website sales@hiwa.cn Email
 This document is the property of Hiuhua Valve Industry Co. Distribution of this document without the written consent of the owner is strictly forbidden. Failure to comply will incur a liability for damages.