



Specification:

- 1.General:ISO5752-2021
- 2.Face to face:ISO5752-2021
- 3.inspection and test:GB/T13927-2022 ISO5208-2015 BS EN12266-1:2012
- 4.Mounting pad:ISO 5211.
- 5.Flange drill:EN1092-2 PN16

DN	L	H1	H2	ISO 5211				EN1092-2 PN16		H3	ØF	HxH
				Top Flange	ØN	ØC1	n1-Ød1	ØC	n-M			
40	33	143	55	F05	65	50	4-Ø8	110	4-M16	29	12.1	9
50	43	143	60	F05	65	50	4-Ø8	125	4-M16	29	12.1	9
65	46	156	68	F05	65	50	4-Ø8	145	4-M16	29	12.1	9
80	46	162	86	F05	65	50	4-Ø8	160	8-M16	29	12.1	9
100	52	181	100	F07	90	70	4-Ø10	180	8-M16	29	14.1	11
125	56	197	111	F07	90	70	4-Ø10	210	8-M16	29	18.1	14
150	56	210	130	F07	90	70	4-Ø10	240	8-M20	29	18.1	14
200	60	240	163	F10	125	102	4-Ø12	295	12-M20	35	22.1	17

NO.	Name	Material
1	Body	DI
2	Disc	SS316/C954
3	Seat	NBR/Vulcanized
4	Stem	SS420

DRN	wang	WEIGHT		MATERIAL	
CHK		SCALE		Butterfly Valve	
APP		DATE	05/06/2025		
hiwa				B23L-HJ	
				REV	250506A

This document is the property of Hiuhua Valve Industry Co.
Distribution of this document without the written consent of the owner is strictly forbidden
Failure to comply will incur a liability for damages

http://www.hiwa.cn Website
sales@hiwa.cn Email

86-533-6077200 Phone
86-533-6077233 FAX

Hiuhua Valve Industry co.
No.36 MinAn Road New Hi-Tech Industry
Zone Zibo Shandong China 255088 p.c